

SPECIFICATIONS

Name	32 Inch Open Frame Touch Monitor
Model	OTL325-RPC04-UHPDA-S-02

LCD Panel Parameters

• Case/Bezel Color	Black Or White
• Display Ratio	16:9
• Backlight Type	LED
• Active Display Area	698.40(H) x 392.85(V) mm
• Native Resolution	1920 x 1080
• Pixel Response Time(Typ.)	8ms
• Colors	16.7M
• Luminance(Typ.)	450nits
• Contrast Ratio (Typ.)	3000:1
• Viewing Angle(cr≥10)	Horizontal(left/right) Typ. 178°(89°/89°) Vertical(up/down) Typ. 178°(89°/89°)
• Backlight Lamp Life(Typ.)	50000 (Hrs To 1/2 Brightness)

Touch Screen Parameters

• Touch Technology	Projected Capacitive Touch (P-Cap)
• Active Touch Area	698.40x392.85 ± 0.5mm
• Glass Thickness	5.3 ± 0.3mm
• Light Transmission	≥83%
• Surface Hardness	≥7H
• Touch Screen Interface	USB
• Touch Point	10
• Glass Type	Tempered Anti-Glare (Optional)

Touch Monitor Parameters

• Mounting Options	VESA : 200x200 mm
• Outline Dimensions	786.1x480.5x62.8mm
• Power Supply	100-240V AC
• On Screen Display (OSD)	Control(back): Power, Auto, Up, Down, Menu
• Power Consumption	MAX :60W
• Temperature Range	Operating: 0°C-40°C,storage: -20°C-60°C
• Humidity (Non Condensing)	Operating: 20%-80%,storage: 10%-90%
• Input Video Signal Connector	VGA,DVI ,DP,HDMI, Audio
• Speakers	2x5W
• Agency Approvals	CE/FCC
• Warranty	1 year
• MTBF	30000 Hrs* (An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit' s reliability; thus MTBF is not, and should not be construed as, a warranty measurement.)