



CDM6240

Single cash dispenser

Description

The single cash dispenser CDM6240 which GRGBanking possesses full independent intellectual property rights, is a high security, large capacity and intelligent CDM for retail ATM, ticket vending machine and other self-service application. It has integrated numbers of world advanced dispensing technologies, and offers high and stable performance at a very low total cost of ownership.

CDM6240

Single cash dispenser

CDM6240 single cash dispenser Module provides 4 advanced features of GRG's leading technology with all independent intellectual property rights owned by GRG.

Reliable

- Opto-Electrical Detecting, able to recognize overlapped, folded, or worn notes.
- High security cassettes and a separate reject tray with lock and seal-leading.
- Unique log record and inquiry function, enables to record and check every transaction

Intelligent

- Cassette low stock detect function to ensure in time cash replenishment, leading to a maximize d uptime.
- Offline Diagnosis system makes troubleshooting very simple
- Radio Frequency Identification technique (Optional), enables to

store the cassette ID, cash loader in formation and loaded cash information

Flexible

- Modular design, easy to assemble and dissemble
- Front or rear service access for convenient maintenance
- Onsite replacement of wearing parts
- High process speed and capacity
- Friction feed, able to handle various currencies
- Dispensing at a high speed of 7 notes per second
- Maximum 2,200 notes per cassette, expandable up to 6 cassettes, 13,200 notes in total

Specification

Electrical specifications

- **Media ranges**
Length: 110mm ~172 mm
Width: 55mm ~85 mm
Thickness: 0.06mm ~0.18 mm
Dispensing system: Friction feed, single dispensing, 7 notes/second
Maximum notes per transaction: 100 notes
Low level detection: 50~250 notes (adjustable)
Reject tray capacity: Single reject, minimum 100 notes
Maintenance: Front/Rear
- **Note Cassette**
Expandability: Up to 6 Cassette capacity: 2200 notes
Security: Mechanical lock and lead sealing
- **Weight**
16.9 Kg, 1 cassette weight, with the increase of every cassette, the weight shall be added by 9.9kg.
Communication interface: RS-232/ USB (optional)
Operating environment
Temperature: 00C~500C Humidity: 20%~90% non-condensing
- **Power supply**
Input voltage : DC 24V, 200W Consumption : Idle 10W; Operating 50W

Dimensions



Front Service Dimensions (mm)



Rear Service Dimensions (mm)

The dimensions above are based on single cassette height, with the increase of every cassette, the height shall be added by 142.5mm.

GRGBanking Equipment Co., Ltd

Add: 9,11 Kelin Road, Science City, High-tech Industrial Development Zone,
Guangzhou, China 51663
Tel: +86 20 6287 9763
Email: oem@grgbanking.com

Copyright by GRGBanking Equipment Co., Ltd.
All rights reserved@201609

Specifications are subject to update without prior notice.
Please consult GRGBanking or its representative for the latest information.