





Description

The CDM8240N bundle dispense module-the fruit of Years of research and development-is a market leading cash dispense module of which GRGBanking possesses full independent intellectual property rights.As a combination of advanced functionalities and a low cost of ownership,the CDM8240N offers superior performance and high reliability whilst it is easy to operate and maintain all this and more makes the CDM8240N an ideal solution for ATMs and other self-service application.



CDM8240N

Cash Dispense Module Maximum performance

CDM8240N cash dispense module provides advanced features of GRG's leading technology with all independent intellectual property rights owned by GRG.

Reliable

- Opto-Electrical Detecting, delivers accurate detection even when notes are severely degraded.
- High security cassettes and a separate reject tray with lock and seal-leading.
- Unique log record and inquiry function, enables to record and check every transaction.
 Intelligent
- Unique self-calibrating function, automatically compensates for assembling errors.
- Offline diagnosis system enables convenient troubleshooting.

- Auto retract function
 Flexible
- Modular design, easy to assemble and dissemble
- Front or rear service access for convenient maintenance
- Extra-long/long/middle/short throat for presenter
- High process speed and capacity
- Friction feed, able to handle various currencies
- Dispensing at a high speed of 7 ~8 notes/ second
- Maximum 3,000~3,500 notes per cassette, expandable up to 6 cassettes, 18,000~21,000 notes in total

Specifications

Media ranges

Length: 110mm ~182 mm Width: 55mm ~85 mm

Thickness: 0.06mm ~0.18 mm

Dispensing system: Friction feed, Bundle dispensing, 7~8 notes/second

- Maximum notes per transaction: 100 notes
- Low level detection: 50~250 notes (adjustable)
- Reject mode: Single/Bundle

Maintenance: Front Access/Rear Access

Note Cassette

Expandability: Up to 6 Cassettes capacity: 3,000~3,500 notes per cassette Reject tray capacity: 250~300(for unfit note reject) + 250~300 (for forgotten Notes retract)

Security: Mechanical lock and lead sealing

Weight

standard throat:32 Kg long throat: 33 Kg (two cassettes weight, with the increase of every cassette, the weight shall be added by 8.8kg.) Communication interface: RS-232/ USB2.0

Operating environment:Temperature: $0\,^\circ\!\!C\!\sim\!\!50\,^\circ\!\!C$ Humidity: 20%~90% non-condensing


Power supply

Voltage: DC 24V±10% Consumption: 200W (in normal temperature)

GRGBanking Equipment Co., Ltd

Add: 9,11 Kelin Road,Science City,High-tech Industrial Development Zone,Guangzhou,China 51663 Tel: +86 2062879763 Email: oem@grgbanking.com

Copyright by GRGBanking Equipment Co., Ltd. All rights reserved@201609



Front Access

The dimensions above are based on 6 cassettes height.With the increase of every cassette, the height shall be added by 142.5mm

Specifications are subject to update without prior notice. Please consult GRGBanking or its representative for the latest information.

www.GRGBanking.com

Dimensions